IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

#/A



RE:

Application of: TUROFF, C.

For:

FLUID-OPERATED POWER TOOL

August 7, 1997

Docket # 76

Hon. Commissioner of Patents & Trademarks Washington, D.C. 20231

Please accept for filing as a new U.S. patent application the following documents which are submitted herewith:

1. <u>X</u>	Exp. Mail Cert.	8	Priority Request
2. <u>X</u>	Specification and Claims	9	Certified Copies
3	Executed Declaration	10	Information Disclosure Statement & PTO 1449
4	Assignment & Recordation Form	11	Foreign Search Report with translation
5	Small Entity Statement	12.	Simultaneous Amendment
6. <u>2</u>	Sheet(s) of Drawings	13. <u>X</u>	Filing Fee
7	Letter re filing without signature + copy of unsigned Declaration	14	Other:

The state of the s

Express Mail Number:

EH949843151US

Date of Deposit:

<u>August 7, 1997</u>

I hereby certify that this paper and the documents referred to herein are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Respectfully submitted,

Ingrud Springer

BE IT KNOWN that I, C. Ross TUROFF, have invented certain new and useful improvements in

FLUID-OPERATED POWER TOOL

of which the following is a complete specification:

BACKGROUND OF THE INVENTION

The present invention relates to fluid-operated power tools.

Fluid-operated power tools, such as for example hydraulic torque wrenches, use a reaction element to react against a neighboring object. Such a reaction element can be formed as a reaction arm which is adjustable in several positions 360° around an axis of the cylinder-piston unit of the power drive. In the known power tool the reaction arm is provided with inner splines which cooperate with outer splines on the cylinder portion of the power drive. However, this has a substantial disadvantage. The outer splines of the cylinder portion in some instances abut themselves against a stationary object, such as for example a wall or the pipe, and the splines can get crushed. As a result, the reaction arm can not be mounted anymore for applications where the reaction arm abuts against an adjacent nut.

5

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a fluid-operated power tool which avoids the disadvantages of the prior art.

In keeping with these objects and with others which will become apparent hereinafter, one feature of the present invention resides, briefly stated, in a fluid-operated power tool which has an engaging part with a turnable engaging element for engaging and turning a threaded connector, and a power drive part with a power drive operative for turning the engaging part, wherein the power drive part includes a fluid-operated cylinder-piston unit, said power drive part having an end spaced from said engaging part and provided with an inner opening with first connecting means; and a reaction member formed as a reaction arm which is turnable between a plurality of positions around an axis of said power drive part and fixable in each of said positions, said reaction arms having a projection which is insertable in said opening and being provided with second connecting means cooperating with said first connecting means so as to connect said reaction arm with said power drive part.

When the fluid-operated power tool is designed in accordance with the present invention, it eliminates the disadvantages of the prior art and provides for the above mentioned highly advantageous results.

The novel features which are considered as characteristic for the present invention are set forth in particular in the appended claims. The invention itself, however, both as to its construction and its method of operation, together with additional objects and advantages thereof, will be best understood from the following description of specific embodiments when read in connection with the accompanying drawings.

5.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a view showing a section of a fluid-operated power tool in accordance with the present invention;

Figure 2 is an end view of the inventive fluid-operated power tool of Figure 1; and

Figure 3 is a view showing a section taken along the line III-III in Figure 1.

5

DESCRIPTION OF PREFERRED EMBODIMENTS

A fluid-operated power tool in accordance with the present invention has a housing which is identified as a whole with reference numeral 1. The tool has an engaging part for engaging and turning a threaded connector such as a bolt, nut and the like. The engaging part has a drive plate 2 provided with an opening in which a ratchet 3 is rotatably supported and engaged by a pawl 4. An engaging projection 6 is provided in the ratchet 3 and supported in sleeves 5.

The fluid-operated power tool further has a power drive part with a power drive for turning the drive plate 2 with the ratchet 4, and thereby the ratchet 3, so as to turn the threaded connector. The power drive includes a cylinder 7 formed in the housing 1, a piston 8 movable in the cylinder, a pivotable slider 10 arranged at the left side of a piston rod of the piston 8 and cooperating with a curved surface of the drive plate 2, and a rod 11 which connects the piston rod of the piston 8 with the drive plate to pull the drive plate back. The right open end of the cylinder 7 of the power-drive part is closed by an end cap 12 having a projecting portion 9.

The fluid-operated power tool further has a reaction arm 13 with an opening in its upper part in Figure 1. A sleeve 14 is arranged in the

20

opening of the reaction arm and extends axially to the left in Figure 1. A portion of the sleeve 14 which extends axially outwardly beyond the reaction arm 1 and is provided with outer connecting means formed for example by a plurality of outer splines OS. In turn, a right end of the cylinder 7 is provided with an inner opening with a plurality of inner splines IS which in the mounted position interengage with the outer splines OS of the sleeve 14. As can be seen from Figure 1, the sleeve 14 has an inner opening 15 with which it is fitted on the projection 9 of the end plug, so that the reaction arm 13 as a whole can be held on the projection 9. Since the splines usually have a relatively loose fit, it is necessary to provide either a large diameter of the splines or a long length of the spline engagement, which however increases a total length of the tool. In contrast, in the applicants invention, the splines are short and at the same time have a small diameter. However, the internal guide formed by the projection 9 prevents side-loading of the splines and their early failure.

The locking mechanism is provided for retaining the reaction arm on the power drive part of the tool. The locking mechanism includes a depression provided in the projection 9 of the end cup and formed for example as a groove 16, and a slider 17 which is movable in a vertical direction in Figure 1 so as to engage in the depression or disengage from it. In the engaged condition the reaction arm 13 is reliably retained on the tool,

while in the disengaged condition when the slider 6 is displaced downwardly beyond the outer contour of the sleeve 14, the arm 13 can be removed from the tool. The engaged condition is obtained by a button 18 which is spring biased upwardly by a spring 19. In order to disengage the slider 17 from the depression 16, an operator presses the button 18 downwardly against the force of the spring 19.

In order to provide an abutment of the reaction arm against a neighboring object in any position, the reaction arm can be removed from the tool, turned by a desired angle, and again mounted on the tool by interengagement of the splines OS and IS, and then locked in this position.

While no inlet and outlet ports are shown for the cylinder-piston unit of the inventive tool, they are well known in the art. In operation when a pressure fluid is admitted into the cylinder 7, it displaces the piston 8 with the piston rod, which in turn turns the drive plate 2 with the pawl 4, and the pawl 4 turns the ratchet 3 and the projection 6 engaged with the threaded connector, so as to turn the threaded connector.

It will be understood that each of the elements described above, or two or more together, may also find a useful application in other types of constructions differing from the types described above.

While the invention has been illustrated and described as embodied in fluid-operated power tool, it is not intended to be limited to the details shown, since various modifications and structural changes may be made without departing in any way from the spirit of the present invention.

Without further analysis, the foregoing will so fully reveal the gist of the present invention that others can, by applying current knowledge, readily adapt it for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the

generic or specific aspects of this invention.

What is claimed as new and desired to be protected by Letters

Patent is set forth in the appended claims.

CLAIMS

1. A fluid-operated power tool, comprising an engaging part with a turnable engaging element for engaging and turning a threaded connector, and a power drive part with a power drive operative for turning the engaging part, wherein the power drive part includes a fluid-operated cylinder-piston unit, said power drive part having an end spaced from said engaging part and provided with an inner opening with first connecting means; and a reaction member formed as a reaction arm which is turnable between a plurality of positions around an axis of said power drive part and fixable in each of said positions, said reaction arms having a projection which is insertable in said opening and being provided with second connecting means cooperating with said first connecting means so as to connect said reaction arm with said power drive part.

2. A fluid-power tool as defined in claim 1, wherein said first connecting means are formed as a plurality of inner splines, said second connecting means being formed as a plurality of outer splines.

3. A fluid-power tool as defined in claim 1, wherein said cylinder-piston unit has an axis, said opening and said projection having axes which coincide with one another and with said axis of said cylinder-piston unit.

4. A fluid-power tool as defined in claim 1; and further comprising guide means provided in said power drive part, said projection with said second connecting means being guided on said guide means.

5. A fluid-power tool as defined in claim 4, wherein said power drive part has an open end, said guide means being formed as an end cap closing said open end.

6. A fluid-power tool as defined in claim 5, wherein said projection with said second connecting means has an inner opening and is fitted with said inner opening on said end cap.

7. A fluid-power tool as defined in claim 6; and further comprising means for locking said reaction arm on said end cap and unlocking said reaction arm from said end cap, said locking end and locking means including a depression formed in said end cap, a slider movable in said reaction arm and engageable in said depression as well as disengageable from said depression, and a button operatable by a user for moving said slider into said depression and releasing said slider from said depression.

8. A fluid-power tool as defined in claim 7; and further comprising spring means which bias said button so as to move said slider into said depression for locking.

ABSTRACT OF THE DISCLOSURE

A fluid-operated power tool has an engaging part with a turnable engaging element for engaging and turning a threaded connector, and a power drive part with a power drive operative for turning the engaging part, wherein the power drive part includes a fluid-operated cylinder-piston unit, the power drive part having an end spaced from the engaging part and provided with an inner opening with a first connection, and a reaction member formed as a reaction arm which is turnable between a plurality of positions around an axis of the power drive part and fixable in each of the positions, the reaction arms having a projection which is insertable in the opening and being provided with second connection with the first connection so as to connect the reaction arm with the power drive part.

COMBINED DECLARATION AND POWER OF ATTORNEY	ATTORNEY DOCKET NO.

As a below-named inventor, I hereby declare that:

C. Ross TUROFF

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention.

FLUID OPERATED POWER TOOL

the specification of which:

(Check one)	X is attached hereto.		
	was filed on		as
	Application Serial No.		and
	was amended on	(if applicable)	
	was amended through _	(if applicable)	

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section § 119, of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application	n(s):	Priority Claimed		
Priority Number	Country	Date filed (Priority Date)	Yes	No
Priority Number	Country	Date filed (Priority Date)	Yes	No
Priority Number	Country	Date filed (Priority Date)	Yes	No

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 35, Code of Federal Regulations, Section 1.56(a), which occurred between the filing date of the prior application and the national or PCT International filing date of this application:

(Application Serial No.)	(Filing Date)	(Status - Patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status - Patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status - Patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that those statements were made with the knowledge that wilful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such wilful false statements may jeopardize the validity of the application or any patent issued thereon.

The undersigned hereby authorizes Robert R. Brunelli and the firm of Sheridan Ross, to accept and follow instructions from:

torc-Up, Inc.

as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between Michael J. Striker, the firm of Striker, Striker & Stenby, and the undersigned. In the event of a change in the persons from whom instructions may be taken, Michael J. Striker and the firm of Striker, Striker & Stenby will be so notified by the undersigned.

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

POWER OF ATTORNEY:

Robert R. Brunelli, Registration No. 39,617

Address all telephone calls to:

Robert R. Brunelli

Telephone number:

(303) 863,9700


Address all correspondence to: Sheridan Ross

Att.: Robert Brunelli
1700 Lincoln Street

Denver, Colorado 80203-4501

U.S.A.

FULL NAME OF SOLE OR FIRST INVENTOR:	INVENTOR'S SIGNATURE:	DATE:
C. Ross TUROFF		
RESIDENCE AND FULL POSTAL ADDRESS: 73 Troutbrook Road Monroe, NY 10950 USA		U.S.



F / G. /

